

Data sheet

PM 007 - Power module (007-1AB00)

Technical data

Order no.	007-1AB00
------------------	------------------

Type	PM 007 - Power module
------	-----------------------

Module ID	-
-----------	---

General information

Note	-
------	---

Features	Output supply Feed-in voltage DC 24 V 10 A Reverse polarity protection Overvoltage protection
----------	---

Technical data power supply

Input voltage (rated value)	DC 24 V
-----------------------------	---------

Input voltage (permitted range)	DC 20.4...28.8 V
---------------------------------	------------------

I _q	-
----------------	---

Current consumption (no-load operation)	-
---	---

Current consumption (rated value)	-
-----------------------------------	---

Max. current drain at backplane bus	-
-------------------------------------	---

Max. current consumption load supply	-
--------------------------------------	---

Max. current drain load supply	-
--------------------------------	---

Short-circuit protection	yes
--------------------------	-----

Efficiency	-
------------	---

Power loss	1 W
------------	-----

Overvoltage protection	36 V
------------------------	------

Status information, alarms, diagnostics

Status display	yes
----------------	-----

Interrupts	no
------------	----

Process alarm	no
---------------	----

Diagnostic interrupt	no
----------------------	----

Diagnostic functions	no
----------------------	----

Diagnostics information read-out	none
----------------------------------	------

Supply voltage display	green LED
------------------------	-----------

Group error display	red LED
---------------------	---------

Channel error display	none
-----------------------	------

Housing

Material	PPE / PPE GF10
----------	----------------

Mounting	Profile rail 35 mm
----------	--------------------

Mechanical data

Dimensions (WxHxD)	12.9 mm x 109 mm x 76.5 mm
--------------------	----------------------------

Net weight	57 g
------------	------

Weight including accessories	57 g
------------------------------	------

Gross weight	71 g
--------------	------

Environmental conditions

Operating temperature	0 °C to 60 °C
-----------------------	---------------

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

Certifications

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes